

FASTRON TECHNO HD

FASTRON TECHNO HD is a synthetic high performance petrol and diesel engine oil.

TYPICAL CHARACTERISTICS

Characteristic	Test Method	FASTRON TECHNO HD
SAE Viscosity Grade	-	5W-30
Appearance	-	Clear
Density at 15 °C, kg/l	ASTM D - 4052	0.8480
Kinematic Viscosity, at 100 °C, cSt	ASTM D - 7279	11.82
Viscosity Index	ASTM D - 2270	174
Flash Point, °C	ASTM D - 92	252
Pour Point, °C	ASTM D - 97	-33
Total Base Number, mgKOH/g	ASTM D - 2896	8

PERFORMANCE LEVEL

FASTRON TECHNO HD meets below performance levels :

- API SN/CF
- ACEA C3
- VW 504.00/507.00
- MB 229.51
- BMW LL-04
- Porsche C30

SUPERIORITIES

- Offers excellent oxidation stability that gives durable performance in all driving condition; high speed, stop and go, or heavy traffic.
- Formulated with high performance additives to provide engine cleanliness and maximum protection from excessive wear.
- Low oil volatility that gives low oil consumption and assures optimum lubrication.
- Compatible with modern exhaust emission system technology
- Support fuel economy improvement.

APPLICATION

FASTRON TECHNO HD is highly recommended for the latest car generation from the leading car manufacturers such as VW, Mercedes Benz, BMW, and Porsche which requires above specifications.

HEALTH AND SAFETY

Please contact our Marketing Head Office, to get Material Safety Data Sheet as information for Health and Safety Protection at work.

Phone: 62-21 3190 7190/5. Fax : 62-21 3148884/601

Website: www.pertaminalubricants.com or email: hsse.ptpl@pertamina.com