

FASTRON TECHNO PLUS

FASTRON TECHNO PLUS is a synthetic high performance gasoline engine oil.

TYPICAL CHARACTERISTICS

Characteristic	Test Method	FASTRON TECHNO PLUS	
SAE Viscosity Grade	-	5W-30	5W-40
Appearance	-	Clear	Clear
Density at 15 °C, kg/l	ASTM D - 4052	0.8480	0.8458
Kinematic Viscosity, at 40 °C, cSt	ASTM D - 7279	69.99	84.90
at 100 °C, cSt	ASTM D - 7279	12.00	14.00
Viscosity Index	ASTM D - 2270	169	170
ASTM Colour	ASTM D - 1500	L 3.0	L 3.0
Flash Point, °C	ASTM D - 92	234	228
Pour Point, °C	ASTM D - 97	-33	-33
Total Base Number, mgKOH/g	ASTM D - 2896	7	7

PERFORMANCE LEVEL

FASTRON TECHNO PLUS meets below performance levels :

- API SP/CF
- ACEA C3
- MB 229.31

SUPERIORITIES

- Offers good oxidation stability that gives durable performance in all driving condition; high speed, stop and go, or heavy traffic.
- Good shear stability and high performance additives to provide engine cleanliness and maximum protection from excessive wear.
- Low oil volatility that gives low oil consumption and assures optimum lubrication.
- Support fuel economy improvement.

APPLICATION

FASTRON TECHNO PLUS is highly recommended for the latest car generation from the leading car manufacturers that operate under extreme condition.

HEALTH AND SAFETY

Please contact our Marketing Head Office to get Material Safety Data Sheet as information for Health and Safety Protection at work.

Phone: 62-21 3190 7190/5. Fax : 62-21 3148884/601

Website: www.pertaminalubricants.com or email: hsse.ptpl@pertamina.com