

PERTAMINA FASTRON TECHNO

SAE 0W-30



Synthetic High-Performance
Petrol & Diesel Engine Oil



Product Description

Pertamina Fastron Techno SAE 0W-30 is a Synthetic High-Performance oil formulated for Petrol and Diesel Engines.

Application

Pertamina Fastron Techno SAE 0W-30 is highly recommended for the latest generation of petrol and diesel engine vehicles from leading manufacturers, specifically with after-treatment emissions devices and that operate under extreme conditions.

Performance Features

- ❖ Stable viscosity that provides optimum acceleration plus superior engine protection during start-up and high temperature operation.
- ❖ Excellent durability against the effects of oxidation and high temperatures to provide a long oil life.
- ❖ Low oil volatility for low oil consumption and optimum lubrication.
- ❖ High quality additives for the prevention of corrosion and piston deposit formation that maintains engine cleanliness resulting in prolonged engine performance and life.
- ❖ Excellent soot control and acid neutralisation for the protection of modern exhaust emissions technologies.

Typical Characteristics

Characteristic	Test Method	Fastron Techno Plus
SAE Viscosity Grade	-	0W-30
Appearance	-	Clear
Density at 15° C, kg/l	ATM D - 4052	0.8422
Kinematic Viscosity at 40° C, cSt	ATM D - 7279	51.57
at 100° C, cSt	ATM D - 7279	10.05
Viscosity Index	ATM D - 2270	186
ASTM Colour	ATM D - 1500	1.5
Flash Point, °C	ATM D - 92	252
Pour Point, °C	ATM D - 5950	-39
Total Base Number, mgKOH/g	ATM D - 2896	8.22

PERTAMINA FASTRON TECHNO SAE 0W-30



Synthetic High-Performance
Petrol & Diesel Engine Oil



Performance Standard

Pertamina Fastron Techno SAE 0W-30 meets the performance level of:

❖ API ACEA C2

Health and Safety

Please contact Pertamina Marketing Head Office for appropriate Material Safety Data Sheet containing information related to Work Health and Safety protection.

Phone: 62-21 3190 7190/5. Fax: 62-21 3148884/601

Website: www.pertaminalubricants.com Email: hsse.ptpl@pertamina.com

Disclaimer:

Information presented in this Product Data Sheet is as accurate as possible prior to printing. Such information is based upon standard industry tests under controlled laboratory conditions and presented as a guide only. To assess product suitability for its intended application, it is recommended that users refer to the latest version of the Product Data Sheet because the information contained herein is subject to change, without notice, due to the upgrades in product formulation, manufacturers' equipment specifications, user applications and storage.