

PERTAMINA

Grease

EPX-NL SERIES

High performance multipurpose lithium soap grease formulated from high quality base oil and latest technology additives.

Gemuk lumas litium serbaguna berkinerja tinggi yang diformulasikan dari base oil berkualitas tinggi dan aditif dengan teknologi terkini.

Typical Characteristics

Characteristics	Test Method	GREASE PERTAMINA EPX-NL SERIES	
NLGI Number	-	1	2
Thickener	-	Lithium 12-Hydroxystearate	Lithium 12-Hydroxystearate
Worked Penetration at 77 °F, 1/10 mm	ASTM D217	310 - 340	265 - 290
Dropping Point, °C	ASTM D2265	Min. 190	Min. 190
Colour	Visual	Yellow	Yellow
Base Oil Viscosity at 40 °C, cSt	ASTM D445	220	220

APPLICATIONS

GREASE PERTAMINA EPX-NL series are recommended for various bearing type and gear in wide range of applications including industrial, automotive, construction and marine, with operating temperature up to 140°C.

PENGUNAAN

GREASE PERTAMINA EPX-NL series direkomendasikan untuk berbagai tipe bearing dan roda gigi dalam berbagai aplikasi termasuk industri, otomotif, konstruksi dan perkapalan, yang beroperasi hingga temperatur 140 °C.

