

PERTAMINA



High performance multipurpose lithium soap grease formulated from high quality base oil and latest technology additives.

Gemuk lumas litium serbaguna berkinerja tinggi yang diformulasikan dari base oil berkualitas tinggi dan aditif dengan teknologi terkini.

Typical Characteristics

Characteristics	Test Method	GREASE PERTAMINA SGX-NL
NLGI Number	-	2
Thickener	-	Lithium 12-Hydroxystearate
Worked Penetration at 77 °F, 1/10 mm	ASTM D217	265 - 290
Dropping Point, °C	ASTM D2265	Min. 190
Colour	Visual	Yellow
Base Oil Viscosity at 40 °C, cSt	ASTM D445	150

SPECIFICATIONS / APPROVALS

- NLGI GC-LB

APPLICATIONS

GREASE PERTAMINA SGX-NL recommended for application on chassis of vehicles, wheel bearings, etc., either for transportation vehicles, light trucks or mini buses.

GREASE PERTAMINA SGX-NL is also recommended for various type of bearings requiring grease with above specification.

SPECIFICATIONS / APPROVALS

- NLGI GC-LB

PENGUNAAN

GREASE PERTAMINA SGX-NL direkomendasikan untuk *chassis* kendaraan, *wheel bearing*, dll., baik untuk kendaraan transportasi, truk tugas ringan atau minibus.

GREASE PERTAMINA SGX-NL juga direkomendasikan untuk berbagai tipe *bearing* yang membutuhkan gemuk lumas dengan spesifikasi di atas.